



**CLASSIC
SERIES**

from
£6,700
+VAT
on Agri Tyres

VST FIELDTRAC 224D

Farmer's All Time Favourite Performer



**POWERFUL 22HP 3-CYLINDER
STAGE-V ENGINE:**
POWERFUL YET ECONOMICAL



LOW TURNING RADIUS:
SUITABLE FOR ORCHARDS, VINEYARDS
& NARROW ROW CROPS



VERSATILE 6+2 TRANSMISSION
CAPABLE OF HANDLING MOST
OF THE EUROPEAN APPLICATIONS



**COMFORTABLE &
ADJUSTABLE SEAT**
OFFERS SUPERIOR COMFORT TO DRIVERS
FOR LONG HOURS OF OPERATION



**DUAL SPOOL VALVE WITH
QUICK RELEASE COUPLERS**
FOR EASY CONNECTIVITY OF
IMPLEMENTS



SMART HYDRAULICS WITH ADDC:
500KGS LIFTING CAPACITY FOR
HEAVY DUTY IMPLEMENTS



www.metcalfsagri.co.uk



sales@metcalfsagri.co.uk



[@metcalfsagri](https://www.facebook.com/metcalfsagri)

TECHNICAL SPECIFICATIONS

ENGINE

Model	K3CE5
Emmission Norm	Stage-V
Type	Naturally Aspirated, Water Cooled 4 Stroke Diesel Engine
No. of Cylinder	3
Engine Power (HP)	22
PTO (HP)	18
Rated RPM	3000
Bore & Stroke (mm)	73 X 78
Displacement (cc)	980
Air Cleaner	Dry Type-Dual Filter
Fuel Tank Capacity (ltrs)	18

TRANSMISSION

Clutch	Dry Single
Gear Box Type	Sliding Mesh
Nos. of Gears	6F+2R
Speed Range- km/hr	Forward: 1.48 - 21.74 Reverse: 1.89- 8.3
Differential Lock (rear)	Standard
Brake Type	Dry Drum
Drive Type	4WD
PTO (rpm)	540 & 1000

ELECTRICALS

Battery	12 V, 72AH, (700 CCA)
Starting system	Starter Motor 12 V , 2 KW
Alternator	12V, 35 AMP

HYDRAULIC SYSTEM

Control Type	ADDC
Pump Capacity (LPM)	12.9
Maximum Lift Capacity (Kgs)	500
3- Point Hitch	Category-I
Steering System	Mechanical/Hydraulic Assisted Power Steering
Rear Spool Valve	2 Valves with Quick Coupling

OTHER FEATURES & DIMENSIONS

Overall Dimensions (LxBxH) with TPL	2225 x 970 x 1185
Ground Clearance (mm)	210
Turning Radius (m)	2.2
Weight (kgs)	880±50
Wheel Base (mm)	1420
Wheel Track (mm)	Front: 890 / 785 Rear: 865 / 740
Front Weight/ Ballast (kgs)	60 (standard Fitment)
Rear Wheel Ballast (kgs)	60 (Optional)
Tire Options (Front & Rear Size)	Agriculture: (5x12,8x18) & (6 x12,8.3 x 20 - Optional) Turf: (23 x 8.5, 33 X 15.5) Industrial: (23 x 8.5-12, 33 X 15.5 - 16.5)
Driver's Seat	Adjustable, European Design Seat
Operating Environment	minus 10 to plus 45 Deg C
Mobile Charging Point	Yes
Silencer (Horizontal Position)	Yes
Battery Cut-off Switch	Yes
ROPS	Yes
Drawbar	Yes (optional)
Hitch Assembly	Yes
Hood Lock with special key	Yes

Optional Extras

- Standard Front Loader Kit
- 4-in-1 Loader Bucket Kit
- Agricultural, Industrial or Turf Tyres

Manufactured by:



Regd. Office.

PLOT NO- 1, DYAVASANDRA INDL. LAYOUT, WHITEFIELD ROAD,
MAHADEVAPURA POST, BENGALURU-560048, KARNATAKA, INDIA.
CIN- L34101KA1967PLC001706

Local Distributor

Metcalf's Agricultural Engineers
The Workshop
Height lane
Chipping
Lancs
PR3 2NU

www.metcalfsagri.co.uk
tel: 01995 61166
sales@metcalfsagri.co.uk



www.metcalfsagri.co.uk

✉ sales@metcalfsagri.co.uk



@metcalfsagri