



**NEW &
STYLISH**

VST FIELDTRAC 918



HEAVY DUTY FRONT AXLE

Compatible with
loaders



COMFORTABLE & ADJUSTABLE SEAT

Offers superior comfort to
drivers for long hours of
operation



LOWEST TURNING RADIUS IN ITS CATEGORY:

Suitable for Orchards,
Vineyards etc.



DUAL PROJECTOR HEADLAMPS

Elegantly embedded in a
new & stylish grill, which gives
better focus & visibility.



VERSATILE 6+2 TRANSMISSION

Capable of handling most of the
Compact Tractor applications



SMART HYDRAULICS WITH ADDC:

500Kgs lifting capacity for
Heavy duty implements.



MOBILE CHARGING

Stay Connected however
long your working hours are.



TURF, INDUSTRIAL & AGRICULTURE TIRE OPTIONS

Available for varied applications.

from
£6,600
+VAT
on Agri Tyres

**NGT
SERIES**



www.metcalfsagri.co.uk



sales@metcalfsagri.co.uk



[@metcalfsagri](https://www.facebook.com/metcalfsagri)

TECHNICAL SPECIFICATIONS

ENGINE

Model	K3CE5
Emmission Norm	Stage-V
Type	Naturally Aspirated, Water Cooled 4, Stroke Diesel Engine
No. of Cylinder	3
Engine Power (HP)	18.5
PTO (HP)	16
Rated RPM	2700
Bore & Stroke (mm)	70 X 78
Displacement (cc)	900
Air Cleaner	Dry Type- Dual Filter
Fuel Tank Capacity (ltrs)	18

TRANSMISSION

Clutch	Dry Single
Gear Box Type	Sliding Mesh
Nos. of Gears	6F+2R
Gear Lever Position	Side Shift
Speed Range- km/hr	Forward: 1.25 - 18.47 Reverse: 1.60 - 7.05
Differential Lock (rear)	Standard
Brake Type	Dry Drum
Drive Type	4WD
PTO (rpm)	540 & 900

ELECTRICALS

Battery	12 V, 73 AH, (700 CCA)
Head Lamp	4 Nos Projector Lamp
Starting system	Starter Motor 12 V , 1.6 KW
Alternator	12V, 35 AMP

HYDRAULIC SYSTEM

Control Type	ADDC
Pump Capacity (LPM)	12.9
Maximum Lift Capacity (Kgs)	500
3- Point Hitch	Category-I
Steering System	Hydraulic Assisted Power Steering
Rear Spool Valve	2 Valves with Quick Coupling

OTHER FEATURES & DIMENSIONS

Overall Dimensions (LxBxH) with TPL & Front Ballast	2820 x 1097 x 2306
Ground Clearance (mm)	190
Turning Radius (m)	2.3
Weight (kgs)	868±50
Wheel Base (mm)	1420
Wheel Track (mm)	Front: 880 / 785 Rear: 870 / 740
Front Weight/ Ballast (kgs)	60 (standard Fitment)
Rear Wheel Ballast (kgs)	60 (Optional)
Tire Options (Front & Rear Size)	Agriculture: (5 x 12 , 8 x 18)
	Turf: (23 x 8.5, 33 X 15.5)
	Industrial: (23 x 8.5-12, 33 X 15.5 - 16.5)
Driver's Seat	Adjustable, European Design Seat
Operating Environment	minus 10 to plus 45 Deg C
Mobile Charging Point	Yes
Silencer (Under Hood)	Yes
Battery Cut-off Switch	Yes
ROPS	Yes
Drawbar	Yes (optional)
Hitch Assembly	Yes
Hood Lock with special key	Yes

Optional Extras

- Standard Front Loader Kit
- 4-in-1 Loader Bucket Kit
- Agricultural, Industrial or Turf Tyres

Manufactured by:



Regd. Office.

PLOT NO- 1, DYAVASANDRA INDL. LAYOUT, WHITEFIELD ROAD,
MAHADEVAPURA POST, BENGALURU-560048, KARNATAKA, INDIA.
CIN- L34101KA1967PLC001706

Authorised distributor

Metcalf's Agricultural Engineers
The Workshop
Height lane
Chipping
Lancs
PR3 2NU

www.metcalfsagri.co.uk
tel: 01995 61166
sales@metcalfsagri.co.uk



www.metcalfsagri.co.uk



sales@metcalfsagri.co.uk



@metcalfsagri