



**CLASSIC
SERIES**

from
£6,200
+VAT
on Agri Tyres

VST FIELDTRAC 180D

Farmer's All Time Favourite Performer.



ROBUST 3-CYLINDER STAGE-V ENGINE

Powerful yet Economical



VERSATILE 6+2 TRANSMISSION

Capable of handling most of the
compact tractor applications



DUAL SPOOL VALVE WITH QUICK RELEASE COUPLERS

For easy connectivity of implements



LOW TURNING RADIUS

Suitable for Orchards, Vineyards and
narrow row crops



COMFORTABLE & ADJUSTABLE SEAT

Offers superior comfort to drivers for
long hours of operation



SMART HYDRAULICS WITH ADDC

500Kgs lifting capacity for Heavy
duty implements

TECHNICAL SPECIFICATIONS

ENGINE

Model	V3DE5
Emmission Norm	Stage-V
Type	Naturally Aspirated, Water Cooled, 4 Stroke Diesel Engine
No.of Cylinder	3
Engine Power (HP)	18.5
PTO (HP)	16
Rated RPM	2700
Bore & Stroke (mm)	70 X 78
Displacement (cc)	900
Air Cleaner	Dry Type-Dual Filter
Fuel Tank Capacity (ltrs)	18

TRANSMISSION

Clutch	Dry Single
Gear Box Type	Sliding Mesh
Nos. of Gears	6F+2R
Speed Range- km/hr	Forward: 1.25 - 18.47 Reverse: 1.60- 7.05
Differential Lock (rear)	Standard
Brake Type	Dry Drum
Drive Type	4WD
PTO (rpm)	540 & 1000

ELECTRICALS

Battery	12 V, 72AH, (700 CCA)
Starting system	Starter Motor 12 V , 2 KW
Alternator	12V, 35 AMP

HYDRAULIC SYSTEM

Control Type	ADDC
Pump Capacity (LPM)	12.9
Maximum Lift Capacity (Kgs)	500
3-Point Hitch	Category-I
Steering System	Mechanical/Hydraulic Assisted Power Steering
Rear Spool Valve	2 Valves with Quick Coupling

OTHER FEATURES & DIMENSIONS

Overall dimensions (LxBxH) with TPL	2275 x 970 x 1185
Ground Clearance (mm)	190
Turning Radius (m)	2.2
Weight (kgs)	860±50
Wheel Base (mm)	1420
Wheel Track (mm)	Front: 890 / 785 Rear: 865 / 740
Front Weight/ Ballast (kgs)	60 (Standard Fitment)
Rear Wheel Ballast (kgs)	60 (Optional)
Tire Options (Front & Rear Size)	Agriculture: (5x12 , 8x18) Turf: (23 x 8.5, 33 X 15.5) Industrial: (23 x 8.5-12, 33 X 15.5 - 12)
Driver's Seat	Adjustable, European Design Seat
Operating Environment	minus 10 to plus 45 Deg C
Mobile Charging Point	Yes
Silencer (Horizontal Position)	Yes
Battery cut-off Switch	Yes
ROPS	Yes
Drawbar	Yes (optional)
Hitch Assembly	Yes
Hood Lock with special key	Yes

Optional Extras

- Standard Front Loader Kit
- 4-in-1 Loader Bucket Kit
- Agricultural, Industrial or Turf Tyres

Manufactured by:



Regd. Office.

PLOT NO- 1, DYAVASANDRA INDL. LAYOUT, WHITEFIELD ROAD,
MAHADEVAPURA POST, BENGALURU-560048, KARNATAKA, INDIA.
CIN- L34101KA1967PLC001706

Local Distributor

Metcalf's Agricultural Engineers
The Workshop
Height lane
Chipping
Lancs
PR3 2NU

www.metcalfsagri.co.uk
tel: 01995 61166
sales@metcalfsagri.co.uk



www.metcalfsagri.co.uk



sales@metcalfsagri.co.uk



@metcalfsagri